



Declaration of Performance

No. 205539-2

according Annex III of the Regulation (EU) No. 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

for the product

ASOCRET-M30

- 1. Unique identification code of the product type:** 205539
- 2. Intended use:** General purpose rendering/
plastering mortar (GP)
- 3. Manufacturer:** Schomburg GmbH & Co. KG
Aquafinstraße 2-8
32760 Detmold
- 4. System or systems of assessment and verification of constancy of performance of the construction product as:** System 4
- 5. Harmonised standard:** DIN EN 998-1:2016
- 6. Notified test laboratory:** not relevant
- 7. Declared performance:**

| Essential characteristic | Performance | System of assessment and verification of constancy of performance | Harmonised technical specification |
|---|---|---|------------------------------------|
| Compressive strength | CS IV | System 4 | DIN EN 998-1:2016 |
| Capillary water uptake 24h, prism | W _c 2 | | |
| Coefficient of water-vapor permeability | ≤ 25 | | |
| Adhesive tensile strength, 28d | ≥ 0,5 N/mm ² | | |
| Image after break | A | | |
| Thermal conductivity (average value λ _{10, dry mat.}), average value from table (P 50%) | < 0,67 | | |
| Fire reaction | A1 | | |
| Durability (frost resistance) | Resistant, by practice according to the technical datasheet | | |

- 8. Appropriate Technical Documentation/Specification:** not relevant



The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Stefan Flügge, technical Department
(name and function)

Detmold, 04.11.2025

The current material safety data sheet and technical data sheet is downloadable under

<http://www.schomburg.de/de/Sicherheitsdatenblatt-datenblaetter.html>

or

http://www.schomburg.de/de/Technisches_Merkblatt-datenblaetter.html